

P300T

Up to 4,95 meters in total safety

P300T platform is a self-propelled scissor lift designed specifically for low-level access and can withstand the demands of everyday use on site while offering enhanced safety features. With its mini dimensions, light weight and its great stability the P300T platform is easy to move by one person only.

- Battery charger indicator
- Forklift pockets
- Easily passes through standard doorway
- Designed for tough site conditions
- Interchangeable between push and self-propelled mode
- Can be driven on slopes of up to 35%

SELF-PROPELLED SMALL SCISSOR LIFT

- Environmentally friendly
- Without CO2 emission or gas leakage
- Low cost maintenance
- 8 hours continuous working

SAFETY

- Saloon- door style entry gates
- Foot brake on rear wheels
- Auto brake system
- Tilt sensor
- Emergency lowering system
- Overload alarm

TECHNICAL DATA

Dimension:

Max. Working Height: 4,95 m | Max. Platform Height: 2,95 m
Overall Width: 765 mm | Overall Length: 1273 mm
Stowed Height: 1776 mm
Work Platform: 631x 1114 mm
Ground Clearance: 50 mm

Performance:

Platform Capacity SWL: 240kg / 1 pers.
Tool Tray Capacity: 20 kg
Raise/ Lower Time: 15 sec
Allowable Cant: 0°- Internal Use
Max Wind Speed: 0 km/h - Internal Use
High resistance powdered paint Orange RAL 2000
Marking and conformity CE- Compliance with the standard EN 280

Power:

Power Source: 24 Volt DC Battery
Charger: 24V - 11A

Weight:

Gross Weight: 460 kg

